


**BILLUND 1 (BIU-90004)**



**Product description**

Small




**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Thermal heat dissipation body
- Single cable entry
- One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency polycarbonate lens
- Integral control gear
- Surge protection 10kV
- Constant lumen output (CLO) and Night-time dimming options


**Optic**



**Product colour**



**Special finishes upon request**



**BILLUND 1 (BIU-90004)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	36 LED
<b>Power</b>	74 W
<b>Lumen</b>	8885 - 10863 lm
<b>Efficacy</b>	120 - 147 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz

<b>Optic</b>	T1, T2, T3, T4, T5
<b>Optic value</b>	142°x128°, 151°x65°, 135°x61°, 102°x63°, 76°x123°
<b>CCT / CRI</b>	3000K CRI70, 4000K CRI70
<b>Bug</b>	B2-U0-G2, B3-U0-G1, B3-U0-G2, B3-U0-G3
<b>ULR</b>	<1%
<b>ULOR</b>	<1%
<b>CIE flux code n°3</b>	95, 96, 97, 99
<b>Dimming type</b>	On/Off, 1-10V, DALI

<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	4.5 kg
<b>Operating temperature</b>	-20 °C to 50 °C
<b>Cable</b>	One IP68 connector supplied with 0.3 m of 3x1.0 sqmm outdoor cable
<b>Through wiring</b>	Single cable entry
<b>Lens / Reflector / Optic</b>	Clear toughened glass, High-efficiency polycarbonate lens