

MALMO 3 (MAL-80211)



Product description

Down - 390 mm



microPrim™


Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Multiple diameters available
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)

- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Down light distribution only
- Wireless control available through Bluetooth connection

- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



Product colour



Special finishes upon request





MALMO 3 (MAL-80211)

Technical information


Material	Aluminium	Input voltage	220-240 V 50/60 Hz	CIE flux code n°3	96, 98
Light source	276 LED	Optic	O, P	Dimming type	On/Off, 1-10V, DALI
Power	26 W	Optic value	107°, 94°	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Lumen	2514 - 3006 lm	CCT / CRI	3000K CRI80, 4000K CRI80		Weight
Efficacy	84 - 100 lm/W	Bug	B1-U0-G1	Operating temperature	-20 °C to 40 °C
Driver option	Integral control gear	ULR	0%	Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	ULOR	0%		

MAL-80211



MALMO 3 (MAL-80211)**Accessory**

Decorative pattern - Type B for
MALMO 400 mm
A92321




Decorative pattern - Type C for
MALMO 400 mm
A93721



Wireless bluetooth converter
A90291



Xpress wireless switch
A90591



Decorative pattern - Type A for
MALMO 400 mm
A90921



DALI Control System
Control-DALI