

**MUNICH 1 (MUN-80001)**



**Product description**

With remote driver



microPrim™


**Luminaire Structure**

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)


- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (included)
- Fire Rated 30 or 60 minutes

- 0dB Acoustic Rated


**Optic**



**Product colour**



**Special finishes upon request**



**MUNICH 1 (MUN-80001)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	7 LED (N,M), 1 LED (W, VW)
<b>Power</b>	12 W
<b>Lumen</b>	509 - 1038 lm
<b>Efficacy</b>	46 - 87 lm/W
<b>Driver option</b>	Remote driver (included)
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz

<b>Optic</b>	N, M, W, VW
<b>Optic value</b>	14°, 25°, 34°, 60°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI
<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	0.4 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>Through wiring</b>	Single cable entry

<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 109,000, 120,000
<b>Lifetime L80B10 (hours)</b>	> 109,000, 120,000
<b>Lifetime L80B50 (hours)</b>	> 109,000, 120,000
<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

MUN-80001



**MUNICH 1** (MUN-80001)

**Accessory**

---



DALI Control System  
**Control-DALI**

---