

NYBRO 5 (NYB-80454)



Product description

Down - 40x80 mm - 2330 mm - Tunable White



microPrim™

Luminaire Structure

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Integral control gear
- Steel brackets for ceiling down mounting option
- Up and down light distribution options
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

NYBRO 5 (NYB-80454)

Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	MacAdam Ellipse	3 SDCM
Light source	288 LED	Optic	O, P	Lifetime L90B10 (hours)	> 23,000
Power	50 W	CCT / CRI	TW (2700K - 6500K)	Lifetime L80B10 (hours)	> 45,000
Lumen	4780 lm	Dimming type	DALI	Lifetime L80B50 (hours)	> 50,000
Efficacy	104 lm/W	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	Variants (DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non- maintained (Z0)
Driver option	Integral control gear				
Driver	Constant current (CC)				
		Weight	5.3 kg		
		Operating temperature	-20 °C to 40 °C		

NYB-80454



NYBRO 5 (NYB-80454)**Accessory**



Ceiling-mounting bracket
A81281



Continuous-coupler bracket
(40/50 mm Down profile)
A81881



DALI Control System
Control-DALI
