


**MATRIX 2 (MT-31406)**



**Product description**

Down (Optic) & Up (Optic 2nd)



microPrim™

**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency optical reflector
- Clear toughened glass
- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible
- MATRIX luminaires with uplight and colder than 3000K CCT do not meet the IDA certification requirements

**Optic**



L / L

**Product colour**



**Special finishes upon request**




**MATRIX 2 (MT-31406)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	1 & 1 COB
<b>Power</b>	12 W
<b>Lumen</b>	158 - 160 lm
<b>Efficacy</b>	13 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz

<b>Optic</b>	L
<b>Optic value</b>	5°
<b>Optic (2nd)</b>	L
<b>Optic (2nd) value</b>	5°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI
<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	2.2 kg

<b>Operating temperature</b>	-20 °C to 40 °C
<b>Through wiring</b>	Single cable entry
<b>Lens / Reflector / Optic</b>	High-efficiency optical reflector, Clear toughened glass
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 50,000
<b>Variants (On/Off, 1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)



**MATRIX 2 (MT-31406)****Accessory**

---



---

Surface mounting box for easy  
cabling (MATRIX 2)  
**SCE-MATRIX-2**

---



---

DALI Control System  
**Control-DALI**

---