

ROY 2 (RY-80081)



Product description


4 Busbar 3 Circuit



Luminaire Structure

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 90°, Rotation 355°
- Propriety lens design for high LOR
- Integral control gear
- Universal adaptor compatible with any track

Optic



Product colour



ROY 2 (RY-80081)

Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	Operating temperature	-20 °C to 40 °C
Light source	5 LED	Optic	N, M, W	MacAdam Ellipse	3 SDCM
Power	9 W	Optic value	19°, 31°, 48°	Lifetime L90B10 (hours)	> 120,000
Lumen	597 - 730 lm	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L80B10 (hours)	> 120,000
Efficacy	66 - 81 lm/W	Dimming type	On/Off	Lifetime L80B50 (hours)	> 120,000
Driver option	Integral control gear	Product colours	Glossy White, Glossy Black	Variants (On/Off)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	Weight	0.6 kg		

RY-80081

