


VIOS 2S (VI-40317)



Product description

With recessing box - Square - Unshielded frame - IK04



microPrim™

Luminaire Structure


- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Frosted toughened glass
- Integral control gear

Optic




G

Product colour



Special finishes upon request



VIOS 2S (VI-40317)

Technical information

Material	Aluminium
Light source	1 COB
Power	5 W
Lumen	209 - 225 lm
Efficacy	42 - 45 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	G
Optic value	92°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U3-G1
ULOR	50%
CIE flux code n°3	64%
Dimming type	On/Off
Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland

Weight	0.6 kg
Operating temperature	-20 °C to 40 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Frosted toughened glass
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 50,000
Variants (On/Off)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

VI-40317

