

LADOR 26 (LD-50141)**Product description**

Thread knuckle mounted - 121x121 mm



microPrim™

Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Thermal heat dissipation body
- Adjustable: Tilt 80° (Up) & 40° (Down), Rotation 350°
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass
- Integral control gear


LADOR 26 (LD-50141)**Technical information**

Material	Aluminium	Driver	Constant current (CC)	Through wiring	Single cable entry
Light source	9 LED	Input voltage	220-240 V 50/60 Hz	Lens / Reflector / Optic	High-efficiency PMMA lens, Clear toughened glass
Power	21 W	Weight	3.0 kg		
Driver option	Integral control gear	Operating temperature	-20 °C to 40 °C		

LADOR 26 (LD-50141)**Accessory**



Anti-glare visor
A53031



Honeycomb louvre
A52021



Linear spread lens
A51314

Please contact the factory for technical details if you wish to use Anti-glare accessories, Colour filters, Lenses and slip glasses in combination.