


MARYS 2 (MY-80021)**Product description**

Ø87 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Propriety lens design for high LOR
- Remote driver (included)

Optic**N** **M** **W****Product colour**

08 - Glossy White (RAL 9010) 09 - Glossy Black (HB451022M)

MARYS 2 (MY-80021)


Technical information

Material	Aluminium
Light source	7 LED
Power	12 W
Lumen	1187 - 1369 lm
Efficacy	99 - 114 lm/W
Driver option	Remote driver (included)

Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	N, M, W
Optic value	15°, 27°, 55°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off, 1-10V, DALI, Trailing edge

Product colours	Glossy White, Glossy Black
Weight	0.4 kg
Operating temperature	-20 °C to 40 °C
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

MY-80021



MARYS 2 (MY-80021)

Accessory



DALI Control System
Control-DALI
