

ATLANTIC 8 (AA-30156-1-1)**Product description**

Medium - Swept shade - Dome top




microPrim™

Luminaire Structure

- Pre-treated before powder coating ensuring high corrosion resistance
- Die-cast aluminium housing
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal toughened glass diffuser
- Integral control gear

Optic

G

Product colour**Special finishes upon request**

ATLANTIC 8 (AA-30156-1-1)


Technical information

Material	Aluminium
Light source	1 COB
Power	41 W
Lumen	2976 - 3134 lm
Efficacy	73 - 76 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	G
Optic value	144°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B1-U3-G1
ULR	3%
ULOR	3%
CIE flux code n°3	91
Dimming type	On/Off, 1-10V, DALI

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	8.9 kg
Operating temperature	-20 °C to 50 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Opal toughened glass diffuser
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

AA-30156-1-1



ATLANTIC 8 (AA-30156-1-1)

Accessory



DALI Control System
Control-DALI
