

ALDO 1 (ALD-30001) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 28x40.7 mm - 500 mm

**Luminaire Structure**

- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256

- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)

- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

Optic

EW

Product colour05 - Matt Silver
(RAL 9006)

ALDO 1 (ALD-30001) (Version 1)**Technical information**

Material	Aluminium	Driver	Constant voltage (CV)	Product colours	Matt Silver
Light source	24 LED	Input voltage	24 VDC	Weight	0.3 kg
Power	6 W	Optic	EW	Operating temperature	-20 °C to 40 °C
Lumen	356 - 381 lm	Optic value	90°	Through wiring	Two cable entries for through wiring
Efficacy	59 - 64 lm/W	CCT / CRI	3000K CRI80, 4000K CRI80	Lens / Reflector / Optic	Clear toughened glass
Driver option	Remote driver (not included)	Dimming type	On/Off		

ALDO 1 (ALD-30001) (Version 1)**Accessory**



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND
