

## ROY 2 (RY-80011)



### Product description


2 Busbar 1 Circuit



### Luminaire Structure

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 90°, Rotation 355°
- Propriety lens design for high LOR
- Integral control gear
- Universal adaptor compatible with any track

### Optic



### Product colour



# ROY 2 (RY-80011)

## Technical information

|               |                       |                 |                            |                         |                                                                                                                 |
|---------------|-----------------------|-----------------|----------------------------|-------------------------|-----------------------------------------------------------------------------------------------------------------|
| Material      | Aluminium             | Input voltage   | 220-240 V 50/60 Hz         | Operating temperature   | -20 °C to 40 °C                                                                                                 |
| Light source  | 5 LED                 | Optic           | N, M, W                    | MacAdam Ellipse         | 3 SDCM                                                                                                          |
| Power         | 9 W                   | Optic value     | 19°, 31°, 48°              | Lifetime L90B10 (hours) | > 120,000                                                                                                       |
| Lumen         | 597 - 730 lm          | CCT / CRI       | 3000K CRI80, 4000K CRI80   | Lifetime L80B10 (hours) | > 120,000                                                                                                       |
| Efficacy      | 66 - 81 lm/W          | Dimming type    | On/Off                     | Lifetime L80B50 (hours) | > 120,000                                                                                                       |
| Driver option | Integral control gear | Product colours | Glossy White, Glossy Black | Variants (On/Off)       | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |
| Driver        | Constant current (CC) | Weight          | 0.6 kg                     |                         |                                                                                                                 |

RY-80011

