


HAYS 2 (HY-80021)**Product description**

Ø107 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Aluminium reflector with white powder coating
- Remote driver (included)

Optic**N** **M** **W****Product colour**


08 - Glossy White (RAL 9010) 09 - Glossy Black (HB451022M)

HAYS 2 (HY-80021)

Technical information

Material	Aluminium	Driver	Constant current (CC)	Product colours	Glossy White, Glossy Black
Light source	7 LED	Input voltage	220-240 V 50/60 Hz	Weight	0.6 kg
Power	12 W	Optic	N, M, W	Operating temperature	-20 °C to 40 °C
Lumen	637 - 804 lm	Optic value	25°, 36°, 39°	Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Efficacy	53 - 67 lm/W	CCT / CRI	3000K CRI80, 4000K CRI80		
Driver option	Remote driver (included)	Dimming type	On/Off, 1-10V, DALI, Trailing edge		

HY-80021



HAYS 2 (HY-80021)

Accessory



DALI Control System
Control-DALI
