

**NYBRO 4 (NYB-80356)**



**Product description**

Down - 60x80 mm - 2330 mm - Trimless - RGBW



microPrim™

**Luminaire Structure**

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Integral control gear
- Stainless steel brackets and screws for mounting
- Down light distribution only
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

**Optic**



**Product colour**




01 - Black (RAL 9011)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)

**Special finishes upon request**



SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban




SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**NYBRO 4 (NYB-80356)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver option</b>	Integral control gear	<b>CCT / CRI</b>	RGBW40
<b>Light source</b>	384 LED	<b>Driver</b>	Constant current (CC)	<b>Dimming type</b>	Bluetooth
<b>Power</b>	84 W	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Product colours</b>	Black, White, Matt Silver, Concrete - Urban, Softscape
<b>Lumen</b>	4000 lm	<b>Optic</b>	O, P		- Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Efficacy</b>	48 lm/W	<b>Optic value</b>	Opal, Micro-prismatic		
				<b>Weight</b>	6.8 kg
				<b>Operating temperature</b>	-20 °C to 40 °C

NYB-80356



**NYBRO 4 (NYB-80356)**

**Accessory**



Continuous-coupler bracket  
(60/70 mm Down & 60 mm  
Down & Up profile)  
**A81581**



Xpress wireless switch  
**A90591**




SLESA-U9, DMX Controller 256  
CH  
**A60491**



SLESA-U11, DMX Controller  
1024 CH  
**A66891**



TPC (Touch Panel Controller) &  
EXT (Extension) 1 Universe  
**A64491**



PoE Connect  
**A64591**



TPC Touch Screen & LPC  
Controller DMX 2 Universe  
**A64691**



DMX/RDM Splitter - 1 channel  
input, 4 channels output  
**A64791**



Cloud Remote Management  
**A64991**



STICK-KE2, DMX Controller 1024  
CH  
**A65091**



TPS Touch Panel Station  
**A65191**



LPCX (Lighting Playback  
Controller X)  
**A66991**



EDN 10 (Ethernet Data Node 10  
Universes)  
**A65391**



DMX splitter & amplifier within  
an IP65 box  
**A63991**



DINA-DR MICRO, DMX Lighting  
Controller & Power Adapter, 60  
CH  
**A67291**