


TUSCON 2 (TS-80021)



Product description


147x579 mm




Luminaire Structure

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Propriety lens design for high LOR
- Remote driver (included)

Optic



Product colour



TUSCON 2 (TS-80021)

Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	Operating temperature	-20 °C to 40 °C
Light source	9 LED	Optic	N, M, W	MacAdam Ellipse	3 SDCM
Power	59 W	Optic value	15°, 26°, 39°	Lifetime L90B10 (hours)	> 120,000
Lumen	4216 - 5132 lm	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L80B10 (hours)	> 120,000
Efficacy	70 - 86 lm/W	Dimming type	On/Off, 1-10V, DALI, Trailing edge	Lifetime L80B50 (hours)	> 120,000
Driver option	Remote driver (included)	Product colours	Glossy White, Glossy Black	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)	
Driver	Constant current (CC)	Weight	3.7 kg	Variants (1-10V, DALI)	

Tuscon 2

