

ATLANTIC 6 (AA-20660-2-2)



Product description

Shepherd's crook - Large - Straight shade - Cone top - IP65 - IK08



microPrim™


Luminaire Structure

- Die-cast aluminium housing
- Extruded aluminium arm bracket
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear UV-stabilised polycarbonate diffuser
- Integral control gear
- Surge protection 10kV

Product colour



Special finishes upon request



ATLANTIC 6 (AA-20660-2-2)

Technical information

Material	Aluminium
Light source	24 LED
Power	40 W
Lumen	3429 - 4222 lm
Efficacy	86 - 106 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	M, W, VW, EW, T2, T3, T4

Optic value	30°, 52°, 66°, 122°, 141°x 51°, 141°x 67°, 98°x 69°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B1-U1-G1, B2-U1-G0, B3-U1-G0
ULR	<1%
ULOR	<1%
CIE flux code n°3	96, 99
Dimming type	On/Off, 1-10V, DALI
Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	13.5 kg

Operating temperature	-20 °C to 40 °C
Through wiring	Single cable entry
Lens / Reflector / Optic	High-efficiency PMMA lens, Clear UV-stabilised polycarbonate diffuser
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 90,000
Lifetime L80B10 (hours)	> 90,000
Lifetime L80B50 (hours)	> 90,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

AA-20660-2-2

