

MALMO 3 (MAL-80244)



Product description

Down - 980 mm - RGBW



microPrim™


Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Multiple diameters available
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)

- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Down light distribution only
- Wireless control available through Bluetooth connection

- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



Product colour



Special finishes upon request



MALMO 3 (MAL-80244)


Technical information

| | |
|----------------------|-----------------------|
| Material | Aluminium |
| Light source | 7488 LED |
| Power | 234 W |
| Lumen | 7077 lm |
| Efficacy | 43 lm/W |
| Driver option | Integral control gear |


| | |
|----------------------|-----------------------|
| Driver | Constant current (CC) |
| Input voltage | 220-240 V 50/60 Hz |
| Optic | O, P |
| Optic value | 107°, 94° |
| CCT / CRI | RGBW40 |
| Dimming type | Bluetooth |

| | |
|------------------------------|---|
| Product colours | Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland |
| Weight | 13.8 kg |
| Operating temperature | -20 °C to 40 °C |
| Variants (Bluetooth) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |


MAL-80244




MALMO 3 (MAL-80244)**Accessory**



Decorative pattern - Type A for
MALMO 1000 mm
A91221



Decorative pattern - Type B for
MALMO 1000 mm
A92621



Decorative pattern - Type C for
MALMO 1000 mm
A94021



Xpress wireless switch
A90591



DALI Control System
Control-DALI
