

MALMO 4 (MAL-90112)



Product description

Down (Optic) & Up (Optic 2nd) - 390 mm



microPrim™

Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Integral control gear
- Stainless steel, adjustable, suspension (1.5 m) complete with electrical wires in white for mounting
- Up and down light distribution options
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban



SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

MALMO 4 (MAL-90112)


Technical information

Material	Aluminium
Light source	276 & 96 LED
Power	46 W
Lumen	4539 - 5279 lm
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	O, P
Optic value	107°, 94°
Optic (2nd)	0
Optic (2nd) value	110°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B2-U4-G1, B2-U5-G1
ULR	19%, 22%

ULOR	19%, 22%
CIE flux code n°3	96, 98
Dimming type	On/Off, 1-10V, DALI
Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	3.0 kg
Operating temperature	-20 °C to 40 °C
Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

MAL-90112



MALMO 4 (MAL-90112)**Accessory**


Supply cable surface mounting
box
A80981




Wireless bluetooth converter
A90291




Xpress wireless switch
A90591



Decorative pattern - Type A for
MALMO 400 mm
A90921



Decorative pattern - Type B for
MALMO 400 mm
A92321



Decorative pattern - Type C for
MALMO 400 mm
A93721



DALI Control System
Control-DALI