

**DUOMO 7** (DU-30136-1-2)



**Product description**

Medium - Swept shade - Cone top




microPrim™


**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal toughened glass diffuser
- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible for DUOMO 6, DUOMO 7

**Product colour**



**Special finishes upon request**



**DUOMO 7** (DU-30136-1-2)

**Technical information**

<b>Material</b>	Aluminium	<b>Optic</b>	G	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	
<b>Light source</b>	1 COB	<b>Optic value</b>	128°			
<b>Power</b>	41 W	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80			
<b>Lumen</b>	1635 - 1654 lm	<b>Bug</b>	B1-U3-G1			
<b>Efficacy</b>	40 lm/W	<b>ULR</b>	15%			
<b>Driver option</b>	Integral control gear	<b>ULOR</b>	15%			
<b>Driver</b>	Constant current (CC)	<b>CIE flux code n°3</b>	87			
<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Dimming type</b>	On/Off, 1-10V, DALI			
					<b>Weight</b>	9.2 kg
					<b>Operating temperature</b>	-20 °C to 40 °C
				<b>Through wiring</b>	Two cable entries for through wiring	
				<b>Lens / Reflector / Optic</b>	Opal toughened glass diffuser	
				<b>MacAdam Ellipse</b>	3 SDCM	
				<b>Lifetime L90B10 (hours)</b>	> 55,000	
				<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)	

DU-30136-1-2

