

**ECO 2 (EC-10505)**



**Product description**

353x160 mm - 800 mm




microPrim™

**Luminaire Structure**

- Die-cast aluminium housing
- Formed sheet aluminium column
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Toughened linear spread lens
- Integral control gear


**Optic**



**Product colour**



**Special finishes upon request**



**ECO 2 (EC-10505)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	3 COB
<b>Power</b>	23 W
<b>Lumen</b>	713 - 769 lm
<b>Efficacy</b>	31 - 33 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	G

<b>Optic value</b>	110°x 61°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B0-U2-G1
<b>ULR</b>	8%
<b>ULOR</b>	8%
<b>CIE flux code n°3</b>	90
<b>Dimming type</b>	On/Off, 1-10V, DALI
<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	9.3 kg


<b>Operating temperature</b>	-20 °C to 40 °C
<b>Cable</b>	One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
<b>Through wiring</b>	Single cable entry
<b>Lens / Reflector / Optic</b>	Toughened linear spread lens
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 50,000
<b>Variants (On/Off, 1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

EC-10505



**ECO 2 (EC-10505)****Accessory**

---



Anchor bolt  
**A10591**



DALI Control System  
**Control-DALI**