

GAVLE 4 (GAV-80423)



Product description

Down - 100x90 mm - 1500 mm - RGBW




microPrim™


Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA diffuser (UGR <19) for glare control
- Integral control gear
- Steel brackets for ceiling down mounting option
- Up and down light distribution options
- Wireless control available through Bluetooth connection


Optic



Product colour



Special finishes upon request



GAVLE 4 (GAV-80423)


Technical information

Material	Aluminium
Light source	3840 LED
Power	133 W
Lumen	5217 lm
Efficacy	39 lm/W
Driver option	Integral control gear


Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	0
Optic value	Opal
CCT / CRI	RGBW40
Dimming type	Bluetooth

Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	13.9 kg
Operating temperature	-20 °C to 40 °C
Variants (Bluetooth)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

GAV-80423



GAVLE 4 (GAV-80423)**Accessory**



Ceiling-mounting bracket (60
mm profile)
A81481



Xpress wireless switch
A90591



DALI Control System
Control-DALI
