


**TOKYO 1 (TOK-80021)****Luminaire Structure**

- Die-cast aluminium housing
- Adjustable: Tilt 90°, Rotation 350°
- With powder coating
- Remote driver (not included)
- With 3-phase universal adapter
- PAR16 GU10 socket, LED and halogen lamps are suitable (up to 30W)


**Optic**

N

M

VW

E

**Product colour**01 - Black (RAL  
9011)03 - White (RAL  
9003)

**TOKYO 1 (TOK-80021)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant voltage (CV)	<b>ULOR</b>	<1%
<b>Light source</b>	MR16-GU10	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>CIE flux code n°3</b>	99
<b>Power</b>	8 W	<b>Optic</b>	N, M, VW, E	<b>Dimming type</b>	On/Off
<b>Lumen</b>	330 - 460 lm	<b>Optic value</b>	13°, 23°, 38°, 51° x 12°	<b>Product colours</b>	Black, White
<b>Efficacy</b>	41 - 58 lm/W	<b>CCT / CRI</b>	3000K CRI95, 4000K CRI90	<b>Weight</b>	1.0 kg
<b>Driver option</b>	Remote driver (not included)	<b>ULR</b>	<1%	<b>Operating temperature</b>	-20 °C to 40 °C

TOK-80021

