



BRISBANE 1 (BRB-95001)**Product description**

Ø60 mm

**Luminaire Structure**

- Extruded aluminium housing with powder coating
- Reflector finishes options (Satin black, Satin gold, Matt white)
- Remote driver (included)
- CRI 95


Optic**Product colour**

BRISBANE 1 (BRB-95001)

Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	CIE flux code n°3	100
Light source	1 COB	Optic	N, M, W	Dimming type	On/Off
Power	10 W	Optic value	24°, 35°, 50°	Product colours	Black, White
Lumen	985 - 1014 lm	CCT / CRI	3000K CRI95, 4000K CRI95	Weight	1.2 kg
Efficacy	99 - 101 lm/W	Bug	B1-U0-G0	Operating temperature	-20 °C to 40 °C
Driver option	Remote driver (included)	ULR	<1%	Reflector finishes options (Satin black, Satin gold, Matt white)	
Driver	Constant current (CC)	ULOR	<1%		

BRB-95001




BRISBANE 1 (BRB-95001)**Accessory**

Reflector finish (Matt white)
A80022-MW



Reflector finish (Satin black)
A80022-SB



Reflector finish (Satin gold)
A80022-SG



Flush-mounted ceiling rose
(Ø100 mm)
A80021