

**MARVIK 5 (MV-30041)**



**Product description**

Ø100 - 220 mm - Down (Optic) & Up (Optic 2nd)



microPrim™


**Luminaire Structure**

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)


- Durable silicone rubber gasket
- High-efficiency optical reflector
- Clear toughened glass
- Integral control gear

- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible
- MARVIK luminaires with uplight and colder than 3000K CCT do not meet the IDA certification requirements


**Optic**



**Product colour**



**Special finishes upon request**



**MARVIK 5 (MV-30041)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	1 & 1 COB
<b>Power</b>	27 W
<b>Lumen</b>	3074 - 3556 lm
<b>Efficacy</b>	114 - 132 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W


<b>Optic value</b>	13°, 23°, 43°
<b>Optic (2nd)</b>	N, M, W
<b>Optic (2nd) value</b>	13°, 23°, 43°
<b>CCT / CRI</b>	2700K CRI80, 3000K CRI80, 4000K CRI80
<b>Bug</b>	B2-U5-G0
<b>ULR</b>	48%, 49%, 50%, 51%
<b>ULOR</b>	48%, 49%, 50%, 51%
<b>Dimming type</b>	On/Off, 1-10V, DALI

**Product colours**  
 Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland

<b>Weight</b>	2.7 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>Through wiring</b>	Single cable entry
<b>Lens / Reflector / Optic</b>	High-efficiency optical reflector, Clear toughened glass
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 61,000

**Variants (On/Off, 1-10V, DALI)**  
 Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

**MV-30041**



**MARVIK 5 (MV-30041)****Accessory**

---



---

Surface mounting box for easy  
cabling (MARVIK 5)  
**SCE-MARVIK-5**

---



---

DALI Control System  
**Control-DALI**

---