

ATLANTIC 9 (AA-30186-2-1)



Product description

Shepherd's crook - Medium - Straight shade - Dome top




microPrim™


Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal toughened glass diffuser
- Integral control gear


Optic



Product colour



Special finishes upon request




ATLANTIC 9 (AA-30186-2-1)

Technical information

Material	Aluminium	Optic	G	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	1 COB	Optic value	134°		Weight
Power	41 W	CCT / CRI	3000K CRI80, 4000K CRI80	Operating temperature	-20 °C to 50 °C
Lumen	3015 - 3174 lm	Bug	B1-U3-G1	Through wiring	Two cable entries for through wiring
Efficacy	74 - 77 lm/W	ULR	3%	Lens / Reflector / Optic	Opal toughened glass diffuser
Driver option	Integral control gear	ULOR	3%	Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	CIE flux code n°3	92		
Input voltage	220-240 V 50/60 Hz	Dimming type	On/Off, 1-10V, DALI		

AA-30186-2-1



ATLANTIC 9 (AA-30186-2-1)

Accessory



DALI Control System
Control-DALI
