

**OULU 9** (OUL-90102)



**Product description**

Down (Optic) & Up (Optic 2nd) - 180° - R250 - Tunable White



microPrim™

**Luminaire Structure**

- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA diffuser (UGR <19) for glare control

- Remote driver (included)
- Stainless steel, adjustable, suspension (1.5 m) complete with electrical wires in white for mounting
- Up and down light distribution options
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options

**Optic**



0

**Product colour**



01 - Black (RAL 9011)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)

**Special finishes upon request**



SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban



SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**OULU 9** (OUL-90102)


**Technical information**

|                      |                          |
|----------------------|--------------------------|
| <b>Material</b>      | Aluminium                |
| <b>Light source</b>  | 144 LED                  |
| <b>Power</b>         | 26 W                     |
| <b>Driver option</b> | Remote driver (included) |
| <b>Driver</b>        | Constant current (CC)    |

|                        |   |
|------------------------|---|
| <b>Input voltage</b>   | 220-240 V 50/60 Hz  |
| <b>Optic</b>           | O   |
| <b>CCT / CRI</b>       | TW (2700K - 6500K)  |
| <b>Dimming type</b>    | DALI  |
| <b>Product colours</b> | Black, White, Matt Silver,<br>Concrete - Urban, Softscape -<br>Urban, Stone - Urban, Corten -<br>Urban, Oak - Woodland, Walnut -<br>Woodland, Pine - Woodland |

|                              |   |
|------------------------------|---|
| <b>Weight</b>                | 2.5 kg  |
| <b>Operating temperature</b> | -20 °C to 40 °C   |
| <b>Variants (DALI)</b>       | Compatible with EN/ IEC<br>60598-2-22: Suitable for<br>emergency installations as<br>central supply, non-maintained<br>(Z0) |

**Oulu 250**



**OULU 9** (OUL-90102)**Accessory**

Supply cable surface mounting  
box  
**A80981**



Wireless bluetooth converter  
**A90291**



Xpress wireless switch  
**A90591**



DALI Control System  
**Control-DALI**