



**AMOS 3 (AM-80041)****Product description**

Ø160 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Aluminium reflector with white powder coating
- Remote driver (included)

**Optic****N**      **M**      **W****Product colour**

08 - Glossy White (RAL 9010)      09 - Glossy Black (HB451022M)

**AMOS 3 (AM-80041)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	18 LED
<b>Power</b>	29 W
<b>Lumen</b>	2336 - 3009 lm
<b>Efficacy</b>	81 - 104 lm/W
<b>Driver option</b>	Remote driver (included)
<b>Driver</b>	Constant current (CC)

<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W
<b>Optic value</b>	26°, 32°, 41°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B2-U0-G0, B3-U0-G0
<b>ULR</b>	<1%
<b>ULOR</b>	<1%

<b>CIE flux code n°3</b>	100, 99
<b>Dimming type</b>	On/Off, 1-10V, DALI
<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	1.6 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lens / Reflector / Optic</b>	Aluminium reflector with white powder coating Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Variants (1-10V)</b>	

**AM-80041**



**AMOS 3** (AM-80041)

**Accessory**

---



DALI Control System  
**Control-DALI**

---