

## GAVLE 4 (GAV-80414)



### Product description

Down - 100x90 mm - 1000 mm - RGBW DMX



microPrim™

### Luminaire Structure


- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA diffuser (UGR <19) for glare control
- Remote driver (included)
- Steel brackets for ceiling down mounting option
- Up and down light distribution options
- Wireless control available through Bluetooth connection

### Optic




0

### Product colour




01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

### Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

# GAVLE 4 (GAV-80414)

## Technical information

|               |                          |               |                       |                       |                                                                                                                                                               |
|---------------|--------------------------|---------------|-----------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material      | Aluminium                | Driver        | Constant current (CC) | Product colours       | Black, White, Matt Silver, Concrete<br>- Urban, Softscape - Urban, Stone<br>- Urban, Corten - Urban, Oak -<br>Woodland, Walnut - Woodland,<br>Pine - Woodland |
| Light source  | 2688 LED                 | Input voltage | 220-240 V 50/60 Hz    | Weight                | 9.0 kg                                                                                                                                                        |
| Power         | 93 W                     | Optic         | O                     | Operating temperature | -20 °C to 40 °C                                                                                                                                               |
| Lumen         | 3470 lm                  | Optic value   | 102°                  | Variants (DMX/RDM)    | Compatible with EN/ IEC<br>60598-2-22: Suitable for<br>emergency installations as<br>central supply, non-maintained<br>(Z0)                                   |
| Efficacy      | 37 lm/W                  | CCT / CRI     | RGBW30, RGBW40        |                       |                                                                                                                                                               |
| Driver option | Remote driver (included) | Dimming type  | DMX, DMX/RDM          |                       |                                                                                                                                                               |

## Gavle 1000



**GAVLE 4** (GAV-80414)

**Accessory**



Recessing box  
**A61051**



DMX Control System  
**Control-DMX**



DMX/RDM Control System  
**Control-DMX-RDM**