



BAKER 1 (BK-80011)



Product description


Ø107 mm




Luminaire Structure

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Aluminium reflector with white powder coating
- Remote driver (included)

Optic



Product colour




BAKER 1 (BK-80011)

Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	Operating temperature	-20 °C to 40 °C
Light source	7 LED	Optic	N, M, W	Lens / Reflector / Optic	Aluminium reflector with white powder coating
Power	12 W	Optic value	19°, 25°, 34°	MacAdam Ellipse	3 SDCM
Lumen	537 - 674 lm	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L90B10 (hours)	> 120,000
Efficacy	45 - 56 lm/W	Dimming type	On/Off, 1-10V, DALI, Trailing edge	Lifetime L80B10 (hours)	> 120,000
Driver option	Remote driver (included)	Product colours	Glossy White, Glossy Black	Lifetime L80B50 (hours)	> 120,000
Driver	Constant current (CC)	Weight	0.7 kg	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)	
				Variants (1-10V, DALI)	

BK-80011



BAKER 1 (BK-80011)

Accessory



DALI Control System
Control-DALI
