


**NORTON 3** (NO-80041)**Product description**

291x291 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Propriety lens design for high LOR
- Remote driver (included)

**Optic****Product colour**

**NORTON 3 (NO-80041)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	4 x 18 LED
<b>Power</b>	126 W
<b>Lumen</b>	9936 - 11348 lm
<b>Efficacy</b>	79 - 90 lm/W
<b>Driver option</b>	Remote driver (included)

<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W
<b>Optic value</b>	15°, 27°, 42°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI

<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	5.1 kg
<b>Operating temperature</b>	-20 °C to 50 °C
<b>Variants (DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

**Norton 3**

