

**NYBRO 10 (NYB-90356)**



**Product description**

Down - 60x95 mm - 2330 mm - RGBW DMX



microPrim™

**Luminaire Structure**

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket

- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Stainless steel brackets and screws for mounting
- Up and down light distribution options
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)
- Track can be integrated into NYBRO products upon request and upon receipt of design drawings

**Optic**



**Product colour**



**Special finishes upon request**




**NYBRO 10 (NYB-90356)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant current (CC)	<b>ULOR</b>	52%, 60%
<b>Light source</b>	384 & 368 LED	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Dimming type</b>	DMX, DMX/RDM
<b>Power</b>	164 W	<b>Optic</b>	O, P	<b>Product colours</b>	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Lumen</b>	11374 lm	<b>CCT / CRI</b>	RGBW40		
<b>Efficacy</b>	92 lm/W	<b>Bug</b>	B1-U5-G0, B1-U5-G1		
<b>Driver option</b>	Integral control gear	<b>ULR</b>	52%, 60%	<b>Weight</b>	8.2 kg
				<b>Operating temperature</b>	-20 °C to 40 °C
				<b>Variants (DMX/RDM)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

NYB-90356



**NYBRO 10 (NYB-90356)****Accessory**

Supply cable surface mounting  
box  
**A80981**



Continuous-coupler bracket  
(60/70 mm Down & 60 mm  
Down & Up profile)  
**A81581**



Integrated track - 3 phase - DALI  
for NYBRO  
**A81491**



Integrated track - 3 phase - On-  
off for NYBRO  
**A81391**



DMX Control System  
**Control-DMX**



DMX/RDM Control System  
**Control-DMX-RDM**