


VICTORIA 2 (VIC-80011)



Product description


Optic arrangement type 2




Luminaire Structure

- Formed sheet steel body with powder coating
- White painted metal sheet
- One size: 600x600 mm
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Integral control gear
- Recessed and surface mounted options
- Accessories: Aluminium frame for surface installation & Aluminium frame for recessed installation of fitting into gypsum plasterboard

Optic



Product colour



03 - White (RAL 9003)

VICTORIA 2 (VIC-80011)


Technical information

Material	Aluminium
Light source	48 LED
Power	10 W
Lumen	1300 lm
Efficacy	130 lm/W

Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	W, VW
Optic value	60°, 90°


CCT / CRI	3000K CRI90, 4000K CRI90
Dimming type	On/Off, DALI
Product colours	White
Weight	2.0 kg
Operating temperature	-20 °C to 40 °C

VIC-80011



VICTORIA 2 (VIC-80011)

Accessory



Frame for recessed installation
of fittings into gypsum
plasterboard ceiling SQUARE
(White)
A83081



Frame for surface installation
SQUARE (White)
A83281



Wireless bluetooth converter
A90291



Xpress wireless switch
A90591



DALI Control System
Control-DALI