


ALDO 2 (ALD-30141) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 500 mm - RGBW

**Luminaire Structure**


- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256
- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

Optic

M

W

E

Product colour

05 - Matt Silver
(RAL 9006)

ALDO 2 (ALD-30141) (Version 1)

Technical information

| | | | | | |
|----------------------|------------------------------|----------------------|-------------------|---------------------------------|--------------------------------------|
| Material | Aluminium | Input voltage | 24 VDC | CIE flux code n°3 | 100, 98, 99 |
| Light source | 9 LED | Optic | M, W, E | Dimming type | DMX, DMX/RDM |
| Power | 18 W | Optic value | 30°, 45°, 25°x40° | Product colours | Matt Silver |
| Lumen | 488 - 492 lm | CCT / CRI | RGBW40 | Weight | 0.9 kg |
| Efficacy | 27 lm/W | Bug | B1-U0-G0 | Operating temperature | -20 °C to 40 °C |
| Driver option | Remote driver (not included) | ULR | <1% | Through wiring | Two cable entries for through wiring |
| Driver | Constant voltage (CV) | ULOR | <1% | Lens / Reflector / Optic | Clear toughened glass |

ALDO 2 (ALD-30141) (Version 1)**Accessory**

DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND