


**BAKER 1 (BK-80011)****Product description**

Ø107 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Aluminium reflector with white powder coating
- Remote driver (included)

**Optic****Product colour**

**BAKER 1 (BK-80011)**

**Technical information**


|                      |                          |
|----------------------|--------------------------|
| <b>Material</b>      | Aluminium                |
| <b>Light source</b>  | 7 LED                    |
| <b>Power</b>         | 12 W                     |
| <b>Lumen</b>         | 537 - 674 lm             |
| <b>Efficacy</b>      | 45 - 56 lm/W             |
| <b>Driver option</b> | Remote driver (included) |
| <b>Driver</b>        | Constant current (CC)    |

|                        |                                    |
|------------------------|------------------------------------|
| <b>Input voltage</b>   | 220-240 V 50/60 Hz                 |
| <b>Optic</b>           | N, M, W                            |
| <b>Optic value</b>     | 19°, 25°, 34°                      |
| <b>CCT / CRI</b>       | 3000K CRI80, 4000K CRI80           |
| <b>Dimming type</b>    | On/Off, 1-10V, DALI, Trailing edge |
| <b>Product colours</b> | Glossy White, Glossy Black         |
| <b>Weight</b>          | 0.7 kg                             |

|                                 |   |
|---------------------------------|---|
| <b>Operating temperature</b>    | -20 °C to 40 °C                               |
| <b>Lens / Reflector / Optic</b> | Aluminium reflector with white powder coating |
| <b>MacAdam Ellipse</b>          | 3 SDCM  |
| <b>Lifetime L90B10 (hours)</b>  | > 120,000                                     |
| <b>Lifetime L80B10 (hours)</b>  | > 120,000                                     |
| <b>Lifetime L80B50 (hours)</b>  | > 120,000                                     |

Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

BK-80011



**BAKER 1** (BK-80011)

**Accessory**

---



DALI Control System  
**Control-DALI**

---