

BRISBANE 8 (BRB-80004)**Product description**

Ø127 mm




optic: W

Luminaire Structure

- Extruded aluminium housing with powder coating
- Reflector finishes options (Satin black, Satin gold, Matt white)
- Thin 1.3mm white polycarbonate trim
- Remote driver (included)
- CRI 95

Optic

W

Product colour

01 - Black (RAL 9011)

03 - White (RAL 9003)

BRISBANE 8 (BRB-80004)


Technical information

Material	Aluminium
Light source	1 COB
Power	43 W
Lumen	3954 - 4033 lm
Efficacy	92 - 94 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)

Input voltage	220-240 V 50/60 Hz
Optic	W
Optic value	55°
CCT / CRI	3000K CRI95, 4000K CRI95
Bug	B3-U0-G0
ULR	<1%
ULOR	<1%

CIE flux code n°3	100
Dimming type	On/Off, DALI
Product colours	Black, White
Weight	3.9 kg
Operating temperature	-20 °C to 40 °C
Lens / Reflector / Optic	Reflector finishes options (Satin black, Satin gold, Matt white), Thin 1.3mm white polycarbonate trim
Variants (On/Off, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

BRB-80004




BRISBANE 8 (BRB-80004)**Accessory**



Reflector finish (Matt white)
A80025-MW



Reflector finish (Satin black)
A80025-SB



Reflector finish (Satin gold)
A80025-SG



DALI Control System
Control-DALI