



**VICTORIA 4** (VIC-80031)**Product description**

Optic arrangement type 4

**Luminaire Structure**

- Formed sheet steel body with powder coating
- White painted metal sheet
- One size: 600x600 mm
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Integral control gear
- Recessed and surface mounted options
- Accessories: Aluminium frame for surface installation & Aluminium frame for recessed installation of fitting into gypsum plasterboard

**Optic****Product colour**

03 - White (RAL 9003)

**VICTORIA 4 (VIC-80031)**

**Technical information**


<b>Material</b>	Aluminium
<b>Light source</b>	3 x 48 LED
<b>Power</b>	25 W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz


<b>Optic</b>	W, VW
<b>Optic value</b>	60°, 90°
<b>CCT / CRI</b>	3000K CRI90, 4000K CRI90
<b>Bug</b>	B2-U1-G1, B3-U1-G1
<b>ULR</b>	0%
<b>ULOR</b>	0%

<b>CIE flux code n°3</b>	99
<b>Dimming type</b>	On/Off, 1-10V, DALI
<b>Product colours</b>	White
<b>Weight</b>	2.0 kg
<b>Operating temperature</b>	-20 °C to 40 °C


**Variants (1-10V)**  
 Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

VIC-80031



**VICTORIA 4** (VIC-80031)**Accessory**

Frame for recessed installation  
of fittings into gypsum  
plasterboard ceiling SQUARE  
(White)  
**A83081**



Frame for surface installation  
SQUARE (White)  
**A83281**



Wireless bluetooth converter  
**A90291**



Xpress wireless switch  
**A90591**



DALI Control System  
**Control-DALI**