

GAVLE 3 (GAV-80101)**Product description**

Down - 60x90 mm - 500 mm




microPrim™

Luminaire Structure


- Extruded aluminium bended profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA diffuser (UGR <19) for glare control
- Integral control gear for On/Off (-ND), DALI (-DA). Remote driver is included for 1-10V (-DI)
- Steel brackets for ceiling down mounting option
- Up and down light distribution options
- Wireless control available through Bluetooth connection

Optic

0

Product colour

01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request

SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban



SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

GAVLE 3 (GAV-80101)
Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	CIE flux code n°3	96	
Light source	192 LED	Optic	0	Dimming type	On/Off, 1-10V, DALI	
Power	26 W	Optic value	102°	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	
Lumen	2352 - 2455 lm	CCT / CRI	3000K CRI80, 4000K CRI80		Weight	3.9 kg
Efficacy	90 - 94 lm/W	Bug	B1-U1-G1		Operating temperature	-20 °C to 40 °C
Driver option	Integral control gear for On/Off (- ND), DALI (-DA). Remote driver is included for 1-10V (-DI)	ULR	0%, <1%	Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)	
Driver	Constant current (CC)	ULOR	0%, <1%			

GAVLE 3 (GAV-80101)**Accessory**

Ceiling-mounting bracket (40 mm profile)
A81381



Wireless bluetooth converter
A90291



Xpress wireless switch
A90591



DALI Control System
Control-DALI