

**LEGEND 2 (LE-40722-A)**



**Product description**

With recessing box - Aluminium frame




microPrim™




**Luminaire Structure**

- Available with interchangeable aluminium or stainless steel grade 316 frames
- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal high-efficiency PMMA diffuser
- Integral control gear


**Optic**



**Product colour**



**Special finishes upon request**



**LEGEND 2 (LE-40722-A)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	3 COB
<b>Power</b>	12 W
<b>Lumen</b>	56 - 60 lm
<b>Efficacy</b>	5 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz

<b>Optic</b>	G
<b>Optic value</b>	109°x54°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B0-U1-G0
<b>ULR</b>	3%
<b>ULOR</b>	3%
<b>CIE flux code n°3</b>	82
<b>Dimming type</b>	On/Off, 1-10V, DALI

<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	2.4 kg
<b>Operating temperature</b>	-20 °C to 45 °C
<b>Through wiring</b>	Two cable entries for through wiring
<b>Lens / Reflector / Optic</b>	Opal high-efficiency PMMA diffuser
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 50,000
<b>Variants (On/Off, 1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

LE-40722-A



**LEGEND 2** (LE-40722-A)

**Accessory**

---



DALI Control System  
**Control-DALI**

---