

**MUSTANG 39 (MS-91182)**



microVos microPrim™


**Luminaire Structure**

- Formed sheet aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry, through wiring upon request


- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass

- Integral control gear


**Optic**



**Product colour**



**Special finishes upon request**




**MUSTANG 39 (MS-91182)**

**Technical information**

<b>Material</b>	Aluminium	<b>Optic value</b>	30°, 52°, 108°, 143°x47°, 140°x71°, 100°x81°	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Light source</b>	24 LED	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Through wiring</b>	Single cable entry, through wiring upon request
<b>Power</b>	54 W	<b>Bug</b>	B1-U0-G1, B2-U0-G0, B2-U0-G2, B3-U0-G0	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Lumen</b>	5777 - 6666 lm	<b>ULR</b>	0%, <1%	<b>MacAdam Ellipse</b>	3 SDCM
<b>Efficacy</b>	107 - 123 lm/W	<b>ULOR</b>	0%, <1%	<b>Lifetime L90B10 (hours)</b>	> 90,000
<b>Driver option</b>	Integral control gear	<b>CIE flux code n°3</b>	97, 99	<b>Lifetime L80B10 (hours)</b>	> 90,000
<b>Driver</b>	Constant current (CC)	<b>Dimming type</b>	On/Off, 1-10V, DALI	<b>Lifetime L80B50 (hours)</b>	> 90,000
<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Optic</b>	M, W, EW, T2, T3, T4		<b>Weight</b>	8.5 kg	

MS-91182



**MUSTANG 39** (MS-91182)

**Accessory**

---



DALI Control System  
**Control-DALI**

---