

TEXAS 1 (TE-10256-2)



Product description

Ø160 - 711 mm - Flat top



microPrim™

Luminaire Structure

- Die-cast aluminium housing
- Extruded aluminium column
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal toughened glass diffuser
- Integral control gear

Optic




G


Product colour




01 - Black (RAL 9011)




02 - Dark Grey (RAL 7043)



03 - White (RAL 9003)




05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)


Special finishes upon request



SU01 - Concrete - Urban




SU02 - Softscape - Urban




SU03 - Stone - Urban




SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland



SW03 - Pine - Woodland

TEXAS 1 (TE-10256-2)


Technical information

Material	Aluminium
Light source	1 COB
Power	41 W
Lumen	471 - 477 lm
Efficacy	11 - 12 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	G
Optic value	130°x 133°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U1-G0
ULR	2%
ULOR	2%
CIE flux code n°3	92
Dimming type	On/Off, 1-10V, DALI

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	7.6 kg
Operating temperature	-20 °C to 40 °C
Through wiring	Single cable entry
Lens / Reflector / Optic	Opal toughened glass diffuser
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 55,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

TE-10256-2



TEXAS 1 (TE-10256-2)

Accessory



Anchor bolt
A10291