


**JASPER 2 (JS-80011)****Product description**

Ø115 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Proprietary lens design for high LOR
- Remote driver (included)

**Optic****Product colour**

**JASPER 2 (JS-80011)**


**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	5 LED
<b>Power</b>	9 W
<b>Lumen</b>	612 - 750 lm
<b>Efficacy</b>	68 - 83 lm/W
<b>Driver option</b>	Remote driver (included)

<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, W
<b>Optic value</b>	19°, 31°, 48°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI, Trailing edge

<b>Product colours</b>	Glossy White, Glossy Black
<b>Weight</b>	0.4 kg
<b>Operating temperature</b>	-20 °C to 50 °C
<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

JS-80011



**JASPER 2 (JS-80011)**

**Accessory**

---



DALI Control System  
**Control-DALI**

---