

LBX 1 (LB-40436)



Product description

Integral control gear - With recessing box - Class I



Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One cable gland supplied with 0.3 m of 3x0.5 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear
- Recessing box is included

Optic



G

Product colour



Special finishes upon request



LBX 1 (LB-40436)

Technical information

Material	Aluminium
Light source	1 LED
Power	4 W
Lumen	39 lm
Efficacy	10 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	G
Optic value	34° x 68°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U1-G0
ULR	4%
ULOR	4%
CIE flux code n°3	97
Dimming type	On/Off

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	0.3 kg
Operating temperature	-20 °C to 40 °C
Cable	One cable gland supplied with 0.3 m of 3x0.5 sqmm outdoor cable
Through wiring	Single cable entry
Lens / Reflector / Optic	Clear toughened glass

LB-40436

