

NYBRO 4 (NYB-80336)



Product description

Down - 60x80 mm - 1466 mm - Trimless - RGBW



microPrim™

Luminaire Structure

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Integral control gear
- Stainless steel brackets and screws for mounting
- Down light distribution only
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

NYBRO 4 (NYB-80336)

Technical information

Material	Aluminium	Driver option	Integral control gear	CCT / CRI	RGBW40
Light source	240 LED	Driver	Constant current (CC)	Dimming type	Bluetooth
Power	53 W	Input voltage	220-240 V 50/60 Hz	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Lumen	2500 lm	Optic	O, P		
Efficacy	47 lm/W	Optic value	Opal, Micro-prismatic		
				Weight	4.5 kg
				Operating temperature	-20 °C to 40 °C

NYB-80336



NYBRO 4 (NYB-80336)

Accessory



Continuous-coupler bracket
(60/70 mm Down & 60 mm
Down & Up profile)
A81581



Xpress wireless switch
A90591




SLESA-U9, DMX Controller 256
CH
A60491



SLESA-U11, DMX Controller
1024 CH
A66891



TPC (Touch Panel Controller) &
EXT (Extension) 1 Universe
A64491



PoE Connect
A64591



TPC Touch Screen & LPC
Controller DMX 2 Universe
A64691



DMX/RDM Splitter - 1 channel
input, 4 channels output
A64791



Cloud Remote Management
A64991



STICK-KE2, DMX Controller 1024
CH
A65091



TPS Touch Panel Station
A65191



LPCX (Lighting Playback
Controller X)
A66991



EDN 10 (Ethernet Data Node 10
Universes)
A65391



DMX splitter & amplifier within
an IP65 box
A63991



DINA-DR MICRO, DMX Lighting
Controller & Power Adapter, 60
CH
A67291