

ALDO 4 (ALD-30201) (Version 1)



Product description

Without remote driver (CV) - Constant voltage (CV) 24 V - 77x95 mm - 500 mm




Luminaire Structure

- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256


- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)

- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

Optic



Product colour



05 - Matt Silver
(RAL 9006)

ALDO 4 (ALD-30201) (Version 1)

Technical information

Material	Aluminium
Light source	18 LED
Power	36 W
Lumen	2317 - 2510 lm
Efficacy	64 - 70 lm/W
Driver option	Remote driver (not included)

Driver	Constant voltage (CV)
Input voltage	24 VDC
Optic	N, M, W, E
Optic value	12°, 30°, 45°, 15°x50°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off

Product colours	Matt Silver
Weight	1.4 kg
Operating temperature	-20 °C to 40 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Clear toughened glass

ALDO 4 (ALD-30201) (Version 1)

Accessory



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND