




For Installation of Lighttalk RGBW inground uplight luminaires.  
Model. LA-60013 and LA-60014


## Product drawing (dimensions)

Walk over 200kg.








CE IP67 IK08 CLASS I



MOUNTING DETAIL



MOUNTING DETAIL



- LIGMAN standard products are supplied with the control gear 220-240V 50/60Hz. The control gear for other voltages and frequencies is available upon request, please consult us for more details.
- LIGMAN luminaires are designed to conform IEC 60598 2-13 standard.




Technical amendments and modifications techniques reserved.

## Ligman Lighting

**Europe Headquarters**  
Ligman Europe s.r.o.  
VGP Park Usti nad Labem, P 2  
Prestanov 113  
403 17 Prestanov  
Czech Republic  
Tel. +420 608 740 504 | sales.cz@ligman.com

**Thailand Headquarters**  
Ligman Lighting Co., Ltd.  
17/2 Moo 4, Monthong, Bangnampreaw  
Chachoengsao 24150 Thailand  
Tel : +66 (2) 7339140  
info@ligman.com

**Ligman Ltd**  
Regus House, Victory Way  
Crossways Business Park  
Dartford DA2 6QD  
Tel. 0800 975 0622  
sales.uk@ligman.com



**Note : Brush finish stainless steel products requirement to wipe the product periodically with a light oil (WD40 or equivalent) to remove any staining.**