

## ALDO 2 (ALD-30041) (Version 1)



### Product description

Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 500 mm



### Luminaire Structure

- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256
- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

## ALDO 2 (ALD-30041) (Version 1)

### Technical information

|                      |                              |                              |                       |                                 |                                      |
|----------------------|------------------------------|------------------------------|-----------------------|---------------------------------|--------------------------------------|
| <b>Material</b>      | Aluminium                    | <b>Driver</b>                | Constant voltage (CV) | <b>Through wiring</b>           | Two cable entries for through wiring |
| <b>Light source</b>  | 9 LED                        | <b>Input voltage</b>         | 24 VDC                | <b>Lens / Reflector / Optic</b> | Clear toughened glass                |
| <b>Power</b>         | 9 W                          | <b>Weight</b>                | 0.8 kg                |                                 |                                      |
| <b>Driver option</b> | Remote driver (not included) | <b>Operating temperature</b> | -20 °C to 40 °C       |                                 |                                      |

**ALDO 2** (ALD-30041) (Version 1)

**Accessory**



Driver (CV) - On/Off - 36 W - IP67  
- 24 V  
**A34491-ND**



Driver (CV) - On/Off - 60 W - IP67  
- 24 V  
**A34591-ND**



Driver (CV) - On/Off - 100 W -  
IP67 - 24 V  
**A34791-ND**



Driver (CV) - On/Off - 150 W -  
IP67 - 24 V  
**A34891-ND**



Driver (CV) - On/Off - 200 W -  
IP67 - 24 V  
**A34991-ND**



Driver (CV) - On/Off - 350 W -  
IP67 - 24 V  
**A35091-ND**