

**NYBRO 8 (NYB-30245)**



**Product description**

Down - 60x80 mm - 1754 mm - Tunable White



microPrim™

**Luminaire Structure**

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Passive thermal management
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)

- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
- Integral control gear
- Up and down light distribution options
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)


**Optic**



**Product colour**



**Special finishes upon request**




**NYBRO 8 (NYB-30245)**

**Technical information**

<b>Material</b>	Aluminium	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>MacAdam Ellipse</b>	3 SDCM
<b>Light source</b>	216 LED	<b>Optic</b>	O, P	<b>Lifetime L90B10 (hours)</b>	> 23,000
<b>Power</b>	55 W	<b>CCT / CRI</b>	TW (2700K - 6500K)	<b>Lifetime L80B10 (hours)</b>	> 45,000
<b>Lumen</b>	4480 lm	<b>Dimming type</b>	DALI	<b>Lifetime L80B50 (hours)</b>	> 50,000
<b>Efficacy</b>	71 lm/W	<b>Product colours</b>	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	<b>Variants (DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non- maintained (Z0)
<b>Driver option</b>	Integral control gear				
<b>Driver</b>	Constant current (CC)	<b>Weight</b>	6.0 kg		
		<b>Operating temperature</b>	-20 °C to 40 °C		

NYB-30245



**NYBRO 8 (NYB-30245)****Accessory**

Continuous-coupler bracket  
(60/70 mm Down & 60 mm  
Down & Up profile)  
**A81581**



Xpress wireless switch  
**A90591**



Wireless bluetooth converter  
**A90291**



DALI Control System  
**Control-DALI**