



ROCKY 3 (RC-80041)**Product description**

147x147 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Adjustable: Tilt 30°
- Propriety lens design for high LOR
- Remote driver (included)

Optic**Product colour**

ROCKY 3 (RC-80041)


Technical information

Material	Aluminium
Light source	18 LED
Power	29 W
Lumen	2484 - 2837 lm
Efficacy	86 - 98 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)

Input voltage	220-240 V 50/60 Hz
Optic	N, M, W
Optic value	15°, 27°, 42°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off, 1-10V, DALI
Product colours	Glossy White, Glossy Black
Weight	1.3 kg

Operating temperature	-20 °C to 40 °C
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000
Variants (DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

RC-80041



ROCKY 3 (RC-80041)

Accessory



DALI Control System
Control-DALI
