


**ALDO 2** (ALD-30041) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 500 mm

**Luminaire Structure**

- Powder coated aluminium alloy housing
- Adjustable aluminium extrusion bracket for ALD-30261, ALD-30262, ALD-30263, ALD-30264, ALD-30265, ALD-30266, ALD-30271, ALD-30272, ALD-30281, ALD-30282, ALD-30291, ALD-30292, ALD-30301, ALD-30302, ALD-30801
- Adjustable galvanised steel bracket for ALD-30241, ALD-30242, ALD-30243, ALD-30244, ALD-30251, ALD-30252, ALD-30253, ALD-30254, ALD-30255, ALD-30256
- Two cable entries for through wiring
- Clear toughened glass
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- For ALD-30001 not included 24 VDC input, DMXRDM address with stable signal

**ALDO 2** (ALD-30041) (Version 1)**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant voltage (CV)	<b>Through wiring</b>	Two cable entries for through wiring
<b>Light source</b>	9 LED	<b>Input voltage</b>	24 VDC	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Power</b>	9 W	<b>Weight</b>	0.8 kg		
<b>Driver option</b>	Remote driver (not included)	<b>Operating temperature</b>	-20 °C to 40 °C		

**ALDO 2** (ALD-30041) (Version 1)**Accessory**

---



---

Driver (CV) - On/Off - 36 W - IP67  
- 24 V  
**A34491-ND**

---



---

Driver (CV) - On/Off - 60 W - IP67  
- 24 V  
**A34591-ND**

---



---

Driver (CV) - On/Off - 100 W -  
IP67 - 24 V  
**A34791-ND**

---



---

Driver (CV) - On/Off - 150 W -  
IP67 - 24 V  
**A34891-ND**

---



---

Driver (CV) - On/Off - 200 W -  
IP67 - 24 V  
**A34991-ND**

---



---

Driver (CV) - On/Off - 350 W -  
IP67 - 24 V  
**A35091-ND**

---