


MARYS 3 (MY-80041)**Product description**

Ø107 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Propriety lens design for high LOR
- Remote driver (included)

Optic**Product colour**

MARYS 3 (MY-80041)


Technical information

| | |
|----------------------|--------------------------|
| Material | Aluminium |
| Light source | 12 LED |
| Power | 19 W |
| Lumen | 1912 - 2286 lm |
| Efficacy | 101 - 120 lm/W |
| Driver option | Remote driver (included) |

| | |
|----------------------|------------------------------------|
| Driver | Constant current (CC) |
| Input voltage | 220-240 V 50/60 Hz |
| Optic | N, M, W |
| Optic value | 14°, 25°, 39° |
| CCT / CRI | 3000K CRI80, 4000K CRI80 |
| Dimming type | On/Off, 1-10V, DALI, Trailing edge |

| | |
|-------------------------------|---|
| Product colours | Glossy White, Glossy Black |
| Weight | 0.8 kg |
| Operating temperature | -20 °C to 40 °C |
| Variants (1-10V, DALI) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |

MY-80041



MARYS 3 (MY-80041)

Accessory



DALI Control System
Control-DALI
